
# 1375191-1 | SL110-5E-L.AL



SL-Series Modular Jack, RJ45, Cat5e Unshielded, Light Almond

This product will be discontinued on: November 30, 2026

## Product Classification

| | |
|---|---|
| **Regional Availability** | Asia \| Australia/New Zealand \| EMEA \| Latin America \| North America |
| **Portfolio** | CommScope® |
| **Product Type** | Modular jack |
| **Product Series** | SL Series |

## General Specifications

| | |
|---|---|
| **ANSI/TIA Category** | 5e |
| **Cable Type** | Unshielded |
| **Color** | Light almond |
| **Conductor Type** | Solid \| Stranded |
| **Integrated Dust Cover Type** | None |
| **Mounting** | SL Series faceplates and panels |
| **Termination Punchdowns, minimum** | 20 times |
| **Termination Tool** | 110 Punchdown tool \| JTT Termination tool |
| **Termination Type** | IDC |
| **Transmission Standards** | ANSI/TIA-568.2-D \| ISO/IEC 11801 Class D |
| **Wiring** | T568A \| T568B |



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: September 16, 2026

## Dimensions

| | |
|---|---|
| **Height** | 16.13 mm \| 0.635 in |
| **Width** | 14.48 mm \| 0.57 in |
| **Depth** | 30.48 mm \| 1.2 in |
| **Compatible Cable Diameter, maximum** | 5.8 mm \| 0.228 in |
| **Compatible Insulated Conductor Diameter, maximum** | 1.45 mm \| 0.057 in |
| **Contact Plating Thickness** | 1.27 µm |
| **Compatible Conductor Gauge, solid** | 22–24 AWG |
| **Compatible Conductor Gauge, stranded** | 24–26 AWG |

## Electrical Specifications

| | |
|---|---|
| **Contact Resistance, maximum** | 20 mOhm |
| **Current Rating at Temperature** | 1.5 A @ 20 °C \| 1.5 A @ 68 °F |
| **Dielectric Withstand Voltage, RMS, contact-to-contact** | 1,000 Vac @ 60 Hz |
| **Insulation Resistance, minimum** | 500 MOhm |
| **Remote Powering** | Fully supports the safe delivery of power over LAN cabling described by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002 |
| **PoE Durability** | Supports IEEE 802.3bt Type 4 (90 W) applications greater than 3000 plug to jack mating cycles |
| **Safety Voltage Rating** | 150 Vac |

## Material Specifications

| | |
|---|---|
| **Contact Base Material** | Beryllium copper |
| **Contact Plating Material** | Gold |
| **IDC Termination Material** | Phosphor Bronze |
| **Material Type** | PC+ABS |
| **Termination Contact Plating** | Tin |



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: September 16, 2026

## Mechanical Specifications

| | |
|---|---|
| **Plug to Jack Mating Cycles** | Complies to IEC 60603-7 series |

## Environmental Specifications

| | |
|---|---|
| **Operating Temperature** | -10 °C to +60 °C (+14 °F to +140 °F) |
| **Storage Temperature** | -40 °C to +70 °C (-40 °F to +158 °F) |
| **Relative Humidity** | Up to 95%, non-condensing |
| **Flammability Rating** | UL 94 V-0 |
| **Safety Standard** | cULus |

## Packaging and Weights

| | |
|---|---|
| **Packaging quantity** | 1 |
| **Packaging Type** | Bag |

## Regulatory Compliance/Certifications

| Agency | Classification |
|---|---|
| CHINA-ROHS | Below maximum concentration value |
| ROHS | Compliant |
| UK-ROHS | Compliant |





©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: September 16, 2026