


1427254-6 | CS31CM BLU C6 4/23 U/UTP RIB 305M



Copper Cable, category 6, 4 pair, UTP, CM rated, 23 AWG, 305 m RIB, blue

Product Classification

Regional Availability	Asia Latin America
Portfolio	NETCONNECT®
Product Type	Twisted pair cable

General Specifications

Product Number	CS31CM
ANSI/TIA Category	6
Cable Component Type	Horizontal
Cable Type	U/UTP (unshielded)
Conductor Type, singles	Solid
Conductors, quantity	8
Jacket Color	Blue
Pairs, quantity	4
Transmission Standards	ANSI/TIA-568.2-D CENELEC EN 50288-6-1 ISO/IEC 11801 Class E

Dimensions

Cable Length	304.8 m 1000 ft
Diameter Over Insulated Conductor	1.029 mm 0.041 in
Diameter Over Jacket, nominal	6.401 mm 0.252 in
Conductor Gauge, singles	23 AWG

Electrical Specifications

Operating Voltage, maximum	80 V
Remote Powering	Fully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

Electrical Performance

1427254-6 | CS31CM BLU C6 4/23 U/UTP RIB 305M

CS CommScope value	IL Insertion Loss (dB/100m)	ACR Attenuation to Crosstalk Ratio (dB/100m)
Std Standard value	RL Return Loss (dB)	ACRF Attenuation to Crosstalk Ratio - Far End (dB/100m)
(listed under the Transmission Standards in the Electrical Specifications above)	NEXT Near End Crosstalk (dB/100m)	PSACR Power Sum Attenuation to Crosstalk Ratio (dB/100m)
Typ Typical value	PSNEXT Power Sum Near End Crosstalk (dB/100m)	PSACRF Insertion Loss (dB/100m)

FREQUENCY	IL TYP	IL CS	IL STD	NEXT TYP	NEXT CS	NEXT STD	ACR TYP	ACR CS	ACR STD	PSNEXT TYP	PSNEXT CS	PSNEXT STD	PSACR TYP	PSACR CS	PSACR STD	ACRF TYP	ACRF CS	ACRF STD	PSACRF TYP	PSACRF CS	PSACRF STD	RL TYP	RL CS	RL STD	TCL TYP	TCL CS	TCL STD	ELTCL TYP	ELTCL CS	ELTCL STD
1.00 MHz			2			74.3			72.3			72.3			70.3			67.8			64.8			20			40			35
10.00 MHz			6			59.3			53.3			57.3			51.3			47.8			44.8			25			40			15
100.00 MHz			19.8			44.3			24.5			42.3			22.5			27.8			24.8			20.1			30			
155.00 MHz			25.2			41.4			16.3			39.4			14.3			24			21			18.8			28.1			
16.00 MHz			7.6			56.2			48.7			54.2			46.7			43.7			40.7			25			38			10.9
20.00 MHz			8.5			54.8			46.3			52.8			44.3			41.8			38.8			25			37			9
200.00 MHz			29			39.8			10.8			37.8			8.8			21.8			18.8			18			27			
25.00 MHz			9.5			53.3			43.8			51.3			41.8			39.8			36.8			24.3			36			7
250.00 MHz			32.8			38.3			5.5			36.3			3.5			19.8			16.8			17.3			26			
31.25 MHz			10.7			51.9			41.2			49.9			39.2			37.9			34.9			23.6			35.1			
4.00 MHz			3.8			65.3			61.5			63.3			59.5			55.8			52.8			23			40			23
62.50 MHz			15.4			47.4			32			45.4			30			31.9			28.9			21.5			32			
8.00 MHz			5.3			60.8			55.4			58.8			53.4			49.9			46.9			24.5			40			16.9

Material Specifications

Conductor Material	Bare copper
Insulation Material	Polyolefin
Jacket Material	PVC

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Flame Test Method	CM

Packaging and Weights

Packaging Type	Reel in box
----------------	-------------

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance

1427254-6 | CS31CM BLU C6 4/23 U/UTP RIB 305M

ROHS	Compliant
UK-ROHS	Compliant

